


REV	CONTENT	CHK	DATE
V0.0	CONTENT	SYJ	25.09.15







Electrical :


	IEC	UL
1.Rated Voltage :	/V	/V
2.Rated Current :	/A	/A
3.Wire Range:	0.5-6mm²	20-8AWG

4.Stripping Length : 10-12mm

5.Operating Temperature : -40°C~ +105°C

6.RoHS Compliance

7."★" is the key quality control point



① Sereies NO.

② Wire diameter
0.5-6mm²
20-8AWG

③ Connection quantity

④ Color: PE-Yellow & Green

Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		⏥	—		//	
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

5	Grounding	XX	2	Copper alloy	Tin Plated
4	CONDUCTOR	XX	1	Copper alloy	Tin Plated
3	BUTTON	XX	3	PBT	SEE NOTE
2	SPRING	XX	3	Stainless Steel	/
1	HOUSING	XX	1	PA66 UL94V-0	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE

DWG.	SYJ	DATE	25.09.15	SIZE	A4	UNITS mm	SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1		
APP.		DATE		NAME	GP6-3-PE		
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.				DWGNO.	XXXX		