
REV	CONTENT	CHK	DATE
V0.0	CONTENT	CXL	20.05.11

Electrical :

	IEC
1.Rated Voltage :	250V
2.Rated Current :	24A
3.Torque Value :	M3 , 0.5N.m
4.Wire Range:	2.5mm^2
5.Stripping Length :	7-8mm
6.Withstanding Voltage :	AC1600V/1Min.
7.Operating Temperature :	-40 °C~+105°C
8.RoHS Compliance	
9.Safty Approval :	
10."★" is the key quality control point.	



Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		÷	—		//
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

4	NUT	S000000610		2	Stainless steel	/	
3	SCREW	S000000410		8	Stainless steel	/	
2	WELDING FOOT	5022B00010		8	Brass	Tin Plated	
1	HOUSING	5022A0YXXA		1	PC+ABS	GREY	
ITEM	NAME OF PART	NO. OF PART		Q"TY	MATERIAL	NOTE	
DWG.	CXL	DATE	20.05.11	SIZE	A4	UNITS mm	SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1		
APP.		DATE		NAME	GT23-7.5-08P-11-00		
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.				DWGNO.	XXXX		