
REV	CONTENT	CHK	DATE
V0.0	CONTENT	SYJ	24.07.26



Electrical :

1.RoHS Compliance

2.Operating Temperature : -40°C~+105°C

3."★" is the key quality control point

GFBS 6 - X- X

① ② ③ ④

① Sereies NO.

② Pitch

③ Poles

2 2Contacts

3 3Contacts

...

10 10Contacts

④ Color:

GY-Grey

BU-Blue

BK-Black

GN-Green

OG-Orange

RD-Red

YE-Yellow

WH-White

PE-Yellow & Green

BE-Beige

Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		⫩	—	//	
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

2	PIN HEADER	XX		2	Copper		Tin plating
1	HOUSING	XX		1	PA66 UL94V-0		SEE NOTE
ITEM	NAME OF PART	NO. OF PART		Q"TY	MATERIAL		NOTE
DWG.	SYJ	DATE	24.07.26	SIZE	A4	UNITS mm	SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1		
APP.		DATE		NAME	GFBS6-X-X		
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.				DWGNO.	XXXX		