


REV	CONTENT	CHK	DATE
V0.0	CONTENT	CXL	20.05.20
V0.1	更新技术参数	LZW	24.07.17







Electrical :

	UL	IEC
1.Rated Voltage :	300V	400V
2.Rated Current :	15A	20A
3.Torque Value :	M2.5 ,3.54Lb.in	M2.5, 0.4N.m
4.Wire Range:	28-12AWG	2.5mm^2

5.Stripping Length : 7-8mm
6.Withstanding Voltage : AC1600V/1Min.
7.Operating Temperature : -40°C~+105°C
8.RoHS Compliance
9.Safty Approval :
10."★" is the key quality control point

2EGTK – 7.62 – XXP – X X – 100
① ② ③ ④ ⑤ ⑥

① Sereies NO.
② Pitch
③ Poles
02 02Contacts
03 03Contacts
...
24 24Contacts
④ 1 Single Pitch
2 Double Pitch
⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White
⑥ Customer Request: 100--Standard

Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		≒	—		//
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

5	SCREW	XX	N	STEEL	Zn Plated
4	BLOCK	XX	N	COPPER ALLOY	Ni Plated
3	CLAMP	XX	N	COPPER ALLOY	Ni Plated
2	COVER	XX	1	PA66 UL94V-0	SEE NOTE
1	HOUSING	XX	1	PA66 UL94V-0	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	CXL DATE 20.05.11		SIZE	A4 UNITS mm	SHEET/OF 1 / 1
CHK.	DATE		SCALE	1:1	
APP.	DATE		NAME	2EGTK-7.62-XXP-XX-100	
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.			DWGNO.	XXXX	