


REV	CONTENT	CHK	DATE
V0.0	CONTENT	MYZ	21.07.02





PCB LAYOUT







SECTION A-A









Electrical :

	UL	IEC
1.Rated Voltage :	300V	450V
2.Rated Current :	20A	24A
3.Torque Value :	M3, 4.43Lb.in	M3 , 0.5N.m
4.Wire Range:	22-12AWG	2.5mm^2

5.Stripping Length : 7-8mm
6.Withstanding Voltage : AC1600V/1Min.
7.Operating Temperature : -40°C~+110°C
8.RoHS Compliance
9.Safty Approval : cULus CE
10."★" is the key quality control point.

GT35R-A - XXP - X X - 00
① ② ③ ④ ⑤

① Sereies No.

② Poles
02 02Contacts
03 03Contacts
...
24 24Contacts

③ 1 Single Pitch
2 Double Pitch

④ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑤ Customer Request : 00--Standard

Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		⏥	—		//
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

1	Housing	XXXXX	1	PA66	UL94V-0	
2	Contact	XXXXX	N	Brass	Tin Plated	
3	Screws	XXXXX	N	Steel	Ni Plated	
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE	
DWG.	MYZ	DATE 21.07.02	SIZE	A4	UNITS mm	SHEET/OF 1 / 1
CHK.		DATE	SCALE	1:1		
APP.		DATE	NAME	GT35R-A-XXP-XX-00		
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.			DWGNO.	XXXX		