


REV	CONTENT	CHK	DATE
V0.0	CONTENT	ZCL	26.03.28



PCB LAYOUT





SCETION A-A

Electrical :

	UL	IEC
1.Rated Voltage :	300V	300V
2.Rated Current :	30A	32A
3.Torque Value :	M4 ,10.53Lb.in	M4, 1.2N.m
4.Wire Range:	22-10AWG	

5.Stripping Length : 12mm
6.Withstanding Voltage : AC4000V/1Min.
7.Operating Temperature : -40°C~+105°C
8.RoHS Compliance
9.Safty Approval : cULus CE
10."★" is the key quality control point

GT65S-B - XXP - X X - 00
① ② ③ ④ ⑤


① Sereies No.


② Poles
02 02Contacts
03 03Contacts
...
24 24Contacts


③ 1 Single Pitch
2 Double Pitch

④ Color:
1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑤ Customer Request : 00--Standard







Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		⏥	—	//	
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

3	SCREW	XX	P	STEEL	Ni Plated	
2	Pin header	XX	P	Copper alloy	Tin Plated	
1	HOUSING	XX	1	PA66	UL94V-0	
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE	
DWG.	ZCL	DATE 26.03.28	SIZE	A4	UNITS mm	SHEET/OF 1 / 1
CHK.		DATE	SCALE	1:1		
APP.		DATE	NAME	GT65S-B-XXP-XX-00		
Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.			DWGNO.	XXXX		