


REV	CONTENT	CHK	DATE
V0.0	CONTENT	CXL	20.05.11



Electrical :

1.Rated Voltage : 300V
2.Rated Current : 10A
3.Wire Range: 22-14AWG
4.Stripping Length : 7-8mm
5.Withstanding Voltage : AC2500V/1Min.
6.Operating Temperature : -40°C~+105°C
7.RoHS Compliance
8. " ★ " is the key quality control point





GT211V - 3.5 -XXP - X X - 00
① ② ③ ④ ⑤ ⑥

① Sereies NO.

② Pitch

③ Poles
02 02Contacts
03 03Contacts
...
24 24Contacts

④ 1 Single Pitch
2 Double Pitch

⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑥ Customer Request: 00--Standard

5	SPRING COIL	XXXXXX	P	STAINLESS STEEL	
4	SOLDER PIN	XXXXXX	P	BRASS	Tin Plated
3	END COVER	XXXXXX	1	PA66(UL94V-0)	SEE NOTE
2	LEVER	XXXXXX	P	PA66(UL94V-0)	SEE NOTE
1	HOUSING	XXXXXX	P	PA66(UL94V-0)	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE

DWG.	CXL	DATE	20.05.11	SIZE	A4	UNITS	mm	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1:1				
APP.		DATE		NAME	GT211V-3.5-XXP-XX-00				

Golten 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD. DWGNO. XXXX

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥		≒	—		//
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 250	over 250 to 350	over 350 to 500	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5